

Fentrim® 230 grey

high-performance adhesive tape



Pre-folded tape for sealing fenestrations and door openings from the outside

Fentrim 230 grey is the optimal solution for permanent airtight and driving-rain proof sealing of window and door frames in solid construction on the exterior. As with all tapes in the Fentrim family, Fentrim 230 grey is a completely primerless solution for all substrates — including masonry.

CHARACTERISTICS

Available widths	2.9", 3.9", 5.9"
Roll length	82 ft
Water vapor transmission	1.72 US perms
Minimum surface contact for masonry substrate	2"

- ✓ extremely high adhesive strength on every surface easy to apply, immediately 100% tight
- ✓ 5/8" pre-folded, without backing strip fastest bonding to window frames
- ✓ bonding from -10°C / 14°F fast and tight window installation all year-round



INSTALLATION INSTRUCTIONS



01

- Apply pre-folded side on window frame



02

- Make sure the tape fully adheres to the window frame and flap down tape



03

- Remove backing paper and apply while applying sufficient pressure



04

- Apply tape along the side of the window frame



05

- Remove backing paper and press on tape



06

- How it should look

All SIGA products are backed by a 10-Year Limited Warranty. Refer to siga.swiss for complete details.

We want you to maximize SIGA's performance potential on your project. Contact one of our Application Advisors for support, from architectural detail review to jobsite training for installers.